

DoP Original Alu 100, ADC2 filling,61-29-CE1031001-2f-en

Declaration	of Perf	ormance:
-------------	---------	----------

Product:	ADC2 filling
GTIN	7320930201531
Size:	1780/2180
Manufacturer:	Inwido Sverige AB, Brogårdsgatan 1, 574 38 Vetlanda
Intended use:	Windows for fitting verticaly in domnestic and commercial buildings
System of assassement and verification of constancy of performance:	System 3
Harmonmized standard:	SS-EN 14351-1:2006+A2:2016
Notified body:	RISE id nr 0402

Performance	Essential properties, Performance	
Watertightness:	9A	
Dangerous substances:	NPD	
Resistance to wind load:	3C	
Load-bearing capatity of safety devices:	Approved	
Accustic performance:	28 dB (-1;-2)	
Thermal transmittance:	1,1	
Air permability:	4	
Dediction managers		
Radiation properties		
Light transmittance (LT):	0,75	

The performance of the product is consistent with the specified performance.

This declaration of performance has been issued in accordance with Regulation (EU) No 305/2011 at the sole responsibility of the manufacturer specified above.

0,6

Signed	on	hefalf	of the	manufacturer:

Solar factor (g):

Name: Viktor Arvidsson

Date: 2024-07-01

City: Vetlanda